


Alfa Laval Compact aseptic filler

Compact aseptic filler for use in the food and beverage industries



Introduction

The compact aseptic filler is designed for filling products into appropriate containers under aseptic conditions.

Application

The compact aseptic filler is particularly well suited for the filling of liquids (such as ready-to-drink juices), dense, low-acid

food and beverage products (such as milk, flavoured milk, milk shakes and sundaes, vegetable and meat extracts) and viscous products containing particulates (such as fruit, citrus and tomato concentrates, syrups and extracts).

Benefits

- Alfa Laval Astepo fillers are based on 30 years of experience in aseptic processing
- A fail safe system is continuously controlling the sterile conditions. In case of an unexpected risk of sterility loss the equipment aborts production and notifies the operator
- The PLC allows to return to production mode only after all the parameters necessary for sterility have been reset successfully.

Design

The compact aseptic filler is pre-assembled and tested as a plug-and-play filler system. The hygienic performance of the dosing valve has the appropriate certification, and the moving parts are protected by hot or cold aseptic barriers.

The filler is built on a strong AISI 304 stainless steel supporting mono-block frame for a 20 inch container and fitted with an operator platform.

The filler is designed with accessories suitable for filling 3–20 litre (1–6 gallons) bags, 200 litre (55 gallons) bags in drums, or 1000 litre (280/300 gallons) in carton boxes over pallets.

With the 1 inch filling head, and accessories for 1 inch caps, the filler is ideal for the filling of liquid, dense and viscous products, and even low-acid products. With the 2 inch filling head, and accessories for 2 inch caps, the filler is ideal for the filling of products containing particulates. The filling head is made of AISI 304 stainless steel.

Parts in contact with product are made of AISI 316 stainless steel. CIP circuit, sterilization circuit and product circuit made of AISI 304/316 stainless steel.

The electrical panel is made of IP55 stainless steel. It contains the PLC control and running system, operator panel, electrical and electro-pneumatic automation systems, as well as an option for remote maintenance.

The compact aseptic filler is fitted with a magnetic flow meter and a diagnostic recorder with removable memory card.



Filling head

Options


- Mass flow meter(s) or balance(s)
- Label printer.

Working principle

Before the filler is used it is automatically washed and sterilized. This procedure is fully automatic, consisting of a CIP phase followed by a sterilization phase, both featuring cyclic action of the valves in contact with the product, the circuit valves and jets of steam. In both phases the time counter is automatically set to zero if any alarm is set off, and does not restart until the condition that triggered the alarm has been reset.

The automatic cycle of opening, filling and closing begins once the bag neck has been manually inserted into the filling head. During this filling cycle, the temperatures of the jets of steam and of the filling valve are carefully monitored and controlled. For low-acid products disinfectant is added as an aerosol spray.

If an automatic bag feeder (ABF) is used to load 3–20 litre (1–6 gallons) bags the automatic loading, opening, filling and closing of the full bag and loading of the next bag begin after the "START CYCLE" button is pressed.



Automatic bag feeder system.

Technical data

- Aseptic-type valves mounted on the product pipe
- Control of the filling batch is carried out by the volumetric or ponderal measuring of the flow. This allows a final accuracy of less than $\pm 0.5\%$ when filling liquid, dense and viscous products
- Alarm signals, which are numbered and described, are visible on the operator's screen
- Temperature monitoring and controls are carried out by a PT 100 unit connected to the PLC, and the results are displayed on the operator's screen.

Aseptic tank/number of filling heads: The use of an aseptic tank is recommended for single-head compact aseptic fillers and also double-head compact aseptic fillers fitted with an automatic bag feeder for liquid, dense and viscous products.

Having the product accumulate in a special aseptic tank allows the sterilizer to operate continuously. This then makes it possible to avoid recycling the product while the full bag is being removed and a new, empty bag is being inserted.

A) Automatic bag feeder for web-type bags from 3–20 litre (1–6 gallons): This is a mobile accessory that can be inserted under one or two filling heads for automatic filling of web-type bags with the 1-inch head. It is possible to reach filling speeds of up to 350 bags per hour (CPH) (3-litre bags) or 200 CPH (20-litre bags) without an operator.

B) Mobile roller conveyor for 3–20 litre (1–6 gallons) bags: This is installed on the supporting framework for the filling head. In the case of manual filling of 3–20 litre (1–6 gallons) bags, use of this conveyor is recommended to ensure better distribution of the product in the bag.

Label printing system makes it possible to print both weights and customized data, as well as a bar code, on standard adhesive white labels supplied from a continuous reel.

C) Accessories for the filling of 200 litre (55 gallons) bags in drums:

- Mobile filling head that can be lowered by 400 mm (15.7 inches) during the filling phase to ensure better distribution of the product within the bag and to reduce manpower costs. It also helps avoid exerting undue stress on the structure of the bag.
- Two clamps to support the bag and avoid excessive force on the weld between the bag and the neck.
- Motorized roller conveyor that makes it easier to replace the full bag with an empty bag.


D) Accessories for the filling of 1000 litre (280/300 gallons) bags (for liquid products):

- Wider frame.
- Motorized roller conveyor (1300 mm [51.2 inches] wide) that makes it easier to replace the full container with an empty container on a pallet.



Compact aseptic filler with 1 filling head.

Dimensional drawing



Weight	kg (lb)
Compact aseptic filler single head / 1-2 inch	1200 (2645)
Compact aseptic filler single head / 1-2 inch + automatic bag feeder system	1500 (3307)
Compact aseptic filler dual heads / 1-2 inch	1800 (3968)
Compact aseptic filler dual heads / 1-2 inch + dual automatic bag feeder systems	2350 (5181)

This document and its contents are subject to copyrights and other intellectual property rights owned by Alfa Laval AB (publ) or any of its affiliates (jointly "Alfa Laval"). No part of this document may be copied, re-produced or transmitted in any form or by any means, or for any purpose, without Alfa Laval's prior express written permission. Information and services provided in this document are made as a benefit and service to the user, and no representations or warranties are made about the accuracy or suitability of this information and these services for any purpose. All rights are reserved.

How to contact Alfa Laval

Up-to-date Alfa Laval contact details for all countries are always available on our website at www.alfalaval.com