



# Alfa Laval Streamline™

## Strainers

### Introduction

The Alfa Laval Streamline™ In-Line Filter/Strainer removes particles from process streams, ensuring product quality and hygiene as well as protecting equipment from clogging, fouling and corrosion. This reduces the risk of unplanned downtime and prolongs equipment maintenance intervals.

Versatile and cost-effective, this filter/strainer with its free-flow design is able to handle a wide range of disposable filter and reusable strainer media, providing maximum application flexibility.

### Application

The Streamline™ In-Line Filter/Strainer is designed to remove particles from process streams thereby promoting product quality and hygiene, while protecting processing equipment, such as homogenizers, meters, spray nozzles, needle valves, and pumps. It is widely used across the dairy, food, beverage, meat and poultry, personal care, and pharmaceutical industries.

### Benefits

- Promotes product quality and hygiene
- Protects processing equipment
- Hygienic, lightweight and corrosion-resistant construction
- Easy to maintain without removing from the process line
- Approved for use in plants that produce meat, poultry, and/or egg products regulated by USDA Food Safety and Inspection Service

### Standard Design

The Streamline™ In-Line Filter/Strainer consists of AISI 316 stainless steel housing, filter or perforated metal single screen or overscreen strainer, pullout top (similar to Mainstream® design), and clamp connections. Available in two lengths to provide optimum filtration area for the application and/or with inlet positioned on the side of the unit.

The Streamline™ In-Line Filter version can be supplied with one of five filtering media, down to 40 microns, including woven and non-woven polypropylene and polyester materials and nylon mesh. The Streamline™ In-Line Strainer version can



be furnished with a single-perforated screen for removing large particles, or with a backup tube and overscreen with small perforations for removing fine particles.

### Working principle

The Streamline™ filters and strainers are designed to promote product quality and sanitation, while protecting processing equipment such as homogenizers, meters, spray nozzles, needle valves, and pumps.

### Cleaning

The Streamline™ housing is approved for CIP (cleaned in place). All internal components must be removed for COP (Cleaned out of place).

Refer to Filter/Strainer instruction manual for complete cleaning instructions.

Warning: Reverse flow or back flushing can result in damage to the internal components.

## TECHNICAL DATA

### Temperature

Temperature range:	250 °F max.
--------------------	-------------

Footnote: (with fluorelastomer gaskets)

### Pressure

Pressure range at 70 °F:	300 PSI
Pressure range at 210 °F:	180 PSI

### Maximum Differential Pressure

Single strainer:	- 50 PSI
Overscreen:	- 25 PSI
Filter:	- 15 PSI

## PHYSICAL DATA

### Materials

Product wetted steel parts:	AISI 316/316L Stainless Steel
Other steel parts:	AISI 304 Stainless Steel
Finish on product contact surfaces:	Ra 32 µ-inch (0.8mm)
Product wetted seals:	Buna, SFY (fluorelastomer)



#### Filtration



Authorized to carry the 3A symbol

Streamline filters can be furnished with any one of five filtering media, down to 40 microns, including woven and non-woven polypropylene and polyester materials and nylon mesh.



#### Fine or Medium Strainer



Authorized to carry the 3A symbol

Complete with a backup tube and overscreen with small perforations for removing finer particles (838 to 1590 microns).




#### Coarse Strainer



Authorized to carry the 3A symbol

Furnished with a single perforated screen for straining large particles.

## Pressure Drop Curves



**Figure 1. Filter Pressure Drop Curves**

Streamline Filters Model 1 and 2


Curve is based on water.

Max. flows for LONG and SHORT units shown.


Curve is typical for all filter socks.

Contact AL for sizing of non-water applications.

## Dimensions



**Figure 3. Side-Entry Streamline**




**Figure 2. Strainer Pressure Drop Curves**

Streamline Strainers Model 1 and 2

Curve is based on water.

Max. flows for LONG and SHORT units shown.

Curve is typical for all perforations.




**Figure 4. Standard Streamline**

## Streamline (inches)

Connection Size	Tri-Clamp® Connections				Outer Assembly		Effective Filter Area (ft. <sup>2</sup> )
	Length (in.) A	Length (in.) B	Length (in.) B1	Length (in.) D	Diameter (in.) C		
Short	1	15 <sup>3/8</sup>	15 <sup>3/4</sup>	22 <sup>1/4</sup>	3 <sup>1/2</sup>	4	0.65
	1½	15 <sup>3/8</sup>	15 <sup>3/4</sup>	22 <sup>1/4</sup>	3 <sup>1/2</sup>	4	0.65
	2	15 <sup>3/8</sup>	15 <sup>3/4</sup>	22 <sup>1/4</sup>	3 <sup>1/2</sup>	4	0.65
	2½	15 <sup>3/8</sup>	15 <sup>3/4</sup>	22 <sup>1/4</sup>	5	4½	0.75
	3	15 <sup>3/8</sup>	15 <sup>3/4</sup>	22 <sup>1/4</sup>	5	4½	0.75
Long	1½	35	35 <sup>3/8</sup>	41 <sup>7/8</sup>	3 <sup>1/2</sup>	4	1.95
	2	35	35 <sup>3/8</sup>	41 <sup>7/8</sup>	3 <sup>1/2</sup>	4	1.95
	2½	35	35 <sup>3/8</sup>	41 <sup>7/8</sup>	5	4½	2.25
	3	35	35 <sup>3/8</sup>	41 <sup>7/8</sup>	5	4½	2.25

## Replacement Strainer Selection


### Perforated Metal Strainer Single Screens

 Authorized to carry the 3A symbol

Screen Part No.	Port Connections	Gauge	Hole Diameter (in.)	Holes Per Square Inch	Percent of Open Area
09G <sup>1</sup>	1, 1 <sup>1/2</sup> , 2 2 <sup>1/2</sup> , 3	14 12	1/4 / .250 1/4 / .250	9 9	58 58
09D	1, 1 <sup>1/2</sup> , 2	16	3/32 / .093	47	33
09E	1, 1 <sup>1/2</sup> , 2 2 <sup>1/2</sup> , 3	14 12	1/8 / .125 1/8 / .125	33 33	40 40
09V	2 <sup>1/2</sup> , 3	12	3/16 / .187	18	51

<sup>1</sup> Note: All strainers using over screens require a backup tube — the recommended type G screen will be furnished as standard backup tube in all Alfa Laval filters and strainers.


### Perforated Metal Over Screens

 Authorized to carry the 3A symbol

Screen Part No.	Gauge	Hole Diameter (in.)	Micron Rating	Holes Per Square Inch	Percent of Open Area
44A	26	.033	838	236	20
44B	26	.050	1270	132	26
44C	26	.062	1590	97	30
44U <sup>1</sup>	26	.040	1015	179	23

<sup>1</sup> Available only in long units.

## Replacement Filter Media Schedule

 Authorized to carry the 3A symbol


Media	Micron Rating <sup>1</sup>	Description
30B	513	100% polyester multifilament
30C	300	Polypropylene and polyester
30D	765	Nylon, 26/29 mesh, rectangular opening, (.025" x .030")
30E	40 - 42	Polypropylene
30G	420	Woven nylon, 40 mesh

<sup>1</sup> Estimated

## Ordering

Please state the following when ordering:

- Filter or strainer
- In-line or side-inlet
- Long or short unit
- Connection size
- Filter or strainer choice

 Authorized to carry the 3A symbol

Streamline units with filters or perforated metal strainers are authorized to carry the 3A symbol.

This document and its contents are subject to copyrights and other intellectual property rights owned by Alfa Laval Corporate AB. No part of this document may be copied, re-produced or transmitted in any form or by any means, or for any purpose, without Alfa Laval Corporate AB's prior express written permission. Information and services provided in this document are made as a benefit and service to the user, and no representations or warranties are made about the accuracy or suitability of this information and these services for any purpose. All rights are reserved.

200006872-1-EN-US

© Alfa Laval Corporate AB

### How to contact Alfa Laval

Up-to-date Alfa Laval contact details for all countries are always available on our website at [www.alfalaval.com](http://www.alfalaval.com)