

Alfa Laval AQ8S

Gasketed plate heat exchanger for HVAC applications

Introduction

Alfa Laval AlfaQ[™] is AHRI Certified® through the Liquid to Liquid Heat Exchangers (LLHE) Certification Program which ensures thermal performance in accordance with the product specifications.

The relatively short plate makes this model suitable for duties with short temperature programs and when a low pressure drop is appreciated. A large range of plate and gasket types is available.

Applications

• HVAC

Benefits

- High energy efficiency low operating cost
- Flexible configuration heat transfer area can be modified
- Easy to install compact design
- High serviceability easy to open for inspection and cleaning and easy to clean by CIP
- Access to Alfa Laval's global service network

Features

Every detail is carefully designed to ensure optimal performance, maximum uptime and easy maintenance. Selection of available features, depending on configuration some features may not be applicable:



- Five-point alignment
- Corner guided alignment system
- Chocolate pattern distribution area
- · Glued gasket
- Clip-on gasket
- Leak chamber
- Bearing boxes
- Fixed bolt head
- Key hole bolt opening
- Lifting lug
- Lining
- Lock washer
- Pressure plate roller
- Tightening bolt cover



Alfa Laval 360° Service Portfolio

Our extensive service offering ensure top performance from your Alfa Laval equipment throughout its life cycle. The Alfa Laval 360 Service Portfolio include installation services, cleaning and repair as well as spare parts, technical documentation and trouble shooting. We also offer replacement, retrofit, integrity testing, monitoring and much more.


For information about our complete service offering and how to contact us - please visit www.alfalaval.com/service.


General remarks for technical information

- The global offering presented in this leaflet may not be available for all regions
- All combinations may not be configurable

Dimensional drawing

Measurements mm (inches)





Frame type	Н	W	h
FM	1405 (55.3")	740 (29.1")	360 (14.2")
FG	1405 (55.3")	800 (31.5")	360 (14.2")
FS	1435 (56.5")	800 (31.5")	390 (15.4")

The number of tightening bolts may vary depending on pressure rating.

Technical data

Plates	Type	Free channel, mm (inches)
М	Single plate	4.0 (0.16)
Materials	1	
		316/316L, 254
Heat transfer plates		C276, C2000
		Ni, Ti, TiPd
Field gask	ets	NBR, EPDM, FKM, HeatSeal
		Carbon steel
Flange connections		Metal lined: stainless steel, Alloy C-276, titanium
		Rubber lined: NBR, EPDM
Frame and pressure plate		Carbon steel, epoxy painted

Other materials may be available on request.

Operational data

Frame type	Max. design pressure barg (psig)	Max. design temperature °C (°F)
FM, PED	10.0 (145)	210 (410)
FM, pvcALS	10.0 (145)	180 (356)
FG, pvcALS	16.0 (232)	180 (356)
FG, ASME	10.3 (150)	250 (482)
FG, PED	16.0 (232)	180 (356)
FS, ASME	31.7 (460)	250 (482)
FS, PED	30.0 (435)	210 (410)

Extended pressure and temperature rating may be available on request.

Flange connections

Frame type	Connection standard
	EN 1092-1 DN200 PN10
FM, pvcALS	ASME B16.5 Class 150 NPS 8
	JIS B2220 10K 200A
FM, PED	EN 1092-1 DN200 PN10
I IVI, FLD	ASME B16.5 Class 150 NPS 8
	EN 1092-1 DN200 PN10
EC pyoAl C	ASME B16.5 Class 150 NPS 8
FG, pvcALS	JIS B2220 10K 200A
	JIS B2220 16K 200A
FG, ASME	ASME B16.5 Class 150 NPS 8
EC DED	EN 1092-1 DN200 PN16
FG, PED	ASME B16.5 Class 150 NPS 8
EC ACME	ASME B16.5 Class 150 NPS 8
FS, ASME	ASME B16.5 Class 300 NPS 8
	EN 1092-1 DN200 PN25
FS, PED	EN 1092-1 DN200 PN40
	ASME B16.5 Class 300 NPS 8

Standard EN1092-1 corresponds to GOST 12815-80 and GB/T9124.1.

Certificates



This document and its contents are subject to copyrights and other intellectual property rights owned by Alfa Laval AB (publ) or any of its affiliates (jointly "Alfa Laval"). No part of this document may be copied, re-produced or transmitted in any form or by any means, or for any purpose, without Alfa Laval's prior express written permission. Information and services provided in this document are made as a benefit and service to the user, and no representations or warranties are made about the accuracy or suitability of this information and these services for any purpose. All rights are reserved.

CHE00104-6-EN-GB © Alfa Laval AB