

Fast Track

Delivered in days,
delivers for decades.



A new way of buying smaller gasketed heat exchangers

Fast track is the first standardized line of plate heat exchangers to guarantee fast, energy efficient results without compromising on quality.

Fast track allows you to instantly place orders from a selection of suitable heat exchangers which will be shipped to you in days.

Easy selection

Our intuitive selection tool eliminates the time spent waiting for calculations. It gives you the opportunity to find the right Fast Track Heat exchanger based on your needs and local market conditions.

Shipment tracking

When you have decided on a Fast Track unit in your own time, the Heat exchangers will be produced and sent within a matter of days. You will be able to follow your delivery using our shipment tracking tools.

Smooth replacement

When your heat exchanger is broken, and you urgently need a replacement our on-line replacement tool allows you to easily convert to one of our Fast Track units. It contains the most common brands and models in the HVAC industry, allowing for a smooth transition to one of our highly efficient Heat exchangers.

The Alfa Laval gasketed plate heat exchanger range

Technical Data



Model	M3	T5	TL3
Height	19"	29"	31"
Width	7"	10"	8"
Length (Depends on number of plates)	16"-25"	6"-14"	16"-54"
Connection	1-1/4" NPT - SS Pipe	2" NPT - SS Pipe	1-1/4" NPT - SS Pipe
Plate Material	0.50mm - 316 Stainless Steel	0.50mm - 316 Stainless Steel	0.50mm - 316 Stainless Steel
Plate Capacity	15-45	15-75	10-50
Max kBtu/h*	Oil Cooling	250	300
	Water to Water Cooling	475	1000
	Water to Water heating	1790	2500

Fast Track are a selection of models from our industrial line. These pre-configured units are suitable for most applications used in HVAC and light industry duties.



Model	TL6	T6	T8	T10
Height	50"	35"	35"	41"
Width	13"	13"	16"	19"
Length (Depends on number of plates)	25"-67"	19"-55"	19"-67"	17"-76"
Connection	2" Studded Port	2" Studded Port	3" Studded Port	4" Studded Port
Plate Material	0.50mm - 316 Stainless Steel	0.50mm - 316 Stainless Steel	0.50mm - 316 Stainless Steel	0.50mm - 316 Stainless Steel
Plate Capacity	20-100	15-70	20-50	20-110
Max kBtu/h*	Oil Cooling	400	700	1520
	Water to Water Cooling	1800	1920	2220
	Water to Water heating	5550	5810	7040

*Btu/h will depend on specific conditions.