

This document and its contents are subject to copyrights and other intellectual property rights owned by Alfa Laval (publ) or any of its affiliates (Alfa Laval). No part of this document may be copied, reproduced or transmitted in any form or by any means, or for any purpose, without Alfa Laval's prior express written permission. Information and services provided in this document are made as a benefit and service to the user, and no representations or warranties are made about the accuracy or suitability of this information and these services for any purpose. All rights are reserved.






FRAME PLATE

Space between pressure plate and supporting column should be kept free from fixed installations!

PRESSURE PLATE
(MOVABLE)

*) Recommended free space for opening and closing to be applied on both sides

**) Free space can be reduced to this distance on one of the sides




APPROX. OUTER DIMENSIONS	
LENGTH	570 mm
WIDTH	410 mm
HEIGHT	900 mm
APPROX. WEIGHTS	
NET WEIGHT, EMPTY	194 kg
WEIGHT FULL OF WATER	211 kg
PLATE MATERIAL	ALLOY 316
PLATE THICKNESS	0.5 mm
GASKET	NBRP ClipGrip™

CHANNEL ARRANGEMENT 1*12 H
/ 1*12 H

NO. OF UNITS 1



DRAWING
GASKETED PLATE HEAT EXCHANGER
T8-MFM
PED Article 4.3



8240114061
Do not use this drawing for foundation bolting or piping layout

DATE 2/8/22
REVISION 0