

# Incalzirea apei de la robinet

Gama de sarcini termice ..... 20-300 kW  
 Intervalul de temperatura de intrare si iesire (partea calda) ..... 80°C-60°C  
 Intervalul de temperatura de intrare si iesire (partea rece) ..... 10°C-55°C

Cadere de presiune maxima ..... 30 kPa  
 Materialul placii ..... Alloy 316  
 Materialul garniturii de etansare .....NBRP

Sarcina termica (kW)	Model Alfa Laval	Numarul articolului	Numar de placi	Tipul de conexiuni
20	T2-BFG-10H	8240125732	10	ISO 7-R 3/4"
40	T2-BFG-10H	8240125732	10	ISO 7-R 3/4"
60	T2-BFG-20H	8240125739	20	ISO 7-R 3/4"
80	M3-FG-15M	8240121680	15	ISO 7-R 1 1/4"
100	M3-FG-20M	8240121681	20	ISO 7-R 1 1/4"
120	M3-FG-20M	8240121681	20	ISO 7-R 1 1/4"
140	M3-FG-25M	8240121682	25	ISO 7-R 1 1/4"
160	M3-FG-25M	8240121682	25	ISO 7-R 1 1/4"
180	TL3-BFG-40L	8240123504	40	ISO 7-R 1 1/4"
200	TL3-BFG-70M	8240123427	70	ISO 7-R 1 1/4"
220	TL3-BFG-80L	8240123515	80	ISO 7-R 1 1/4"
240	TL3-BFG-80L	8240123515	80	ISO 7-R 1 1/4"
260	TL3-BFG-80L	8240123515	80	ISO 7-R 1 1/4"
280	TL3-BFG-80L	8240123515	80	ISO 7-R 1 1/4"
300	T5-BFG-30L	8240124395	30	ISO 228-G 2" B

Gama de sarcini termice ..... 20-300 kW  
 Intervalul de temperatura de intrare si iesire (partea calda) ..... 80°C-50°C  
 Intervalul de temperatura de intrare si iesire (partea rece) ..... 10°C-55°C

Cadere de presiune maxima ..... 30 kPa  
 Materialul placii ..... Alloy 316  
 Materialul garniturii de etansare .....NBRP

Sarcina termica (kW)	Model Alfa Laval	Numarul articolului	Numar de placi	Tipul de conexiuni
20	T2-BFG-10H	8240125732	10	ISO 7-R 3/4"
40	T2-BFG-10H	8240125732	10	ISO 7-R 3/4"
60	T2-BFG-15H	8240125735	15	ISO 7-R 3/4"
80	T2-BFG-15H	8240125735	15	ISO 7-R 3/4"
100	T2-BFG-20H	8240125739	20	ISO 7-R 3/4"
120	M3-FG-20M	8240121681	20	ISO 7-R 1 1/4"
140	M3-FG-25M	8240121682	25	ISO 7-R 1 1/4"
160	M3-FG-25M	8240121682	25	ISO 7-R 1 1/4"
180	M3-FG-30H	8240121694	30	ISO 7-R 1 1/4"
200	M3-FG-35H	8240121695	35	ISO 7-R 1 1/4"
220	TL3-BFG-30L	8240123495	30	ISO 7-R 1 1/4"
240	TL3-BFG-35L	8240123500	35	ISO 7-R 1 1/4"
260	TL3-BFG-40L	8240123504	40	ISO 7-R 1 1/4"
280	TL3-BFG-40L	8240123504	40	ISO 7-R 1 1/4"
300	TL3-BFG-70M	8240123427	70	ISO 7-R 1 1/4"

## Incalzirea apei de la robinet

Gama de sarcini termice ..... 20-300 kW  
 Intervalul de temperatura de intrare si iesire (partea calda) ..... 80°C-40°C  
 Intervalul de temperatura de intrare si iesire (partea rece) ..... 10°C-55°C

Cadere de presiune maxima ..... 30 kPa  
 Materialul placii ..... Alloy 316  
 Materialul garniturii de etansare .....NBRP

Sarcina termica (kW)	Model Alfa Laval	Numarul articolului	Numar de placi	Tipul de conexiuni
20	T2-BFG-10H	8240125732	10	ISO 7-R 3/4"
40	T2-BFG-10H	8240125732	10	ISO 7-R 3/4"
60	T2-BFG-15H	8240125735	15	ISO 7-R 3/4"
80	T2-BFG-20H	8240125739	20	ISO 7-R 3/4"
100	M3-FG-20M	8240121681	20	ISO 7-R 1 1/4"
120	M3-FG-20M	8240121681	20	ISO 7-R 1 1/4"
140	M3-FG-20M	8240121681	20	ISO 7-R 1 1/4"
160	M3-FG-25M	8240121682	25	ISO 7-R 1 1/4"
180	M3-FG-25M	8240121682	25	ISO 7-R 1 1/4"
200	M3-FG-30H	8240121694	30	ISO 7-R 1 1/4"
220	M3-FG-30H	8240121694	30	ISO 7-R 1 1/4"
240	M3-FG-35H	8240121695	35	ISO 7-R 1 1/4"
260	TL3-BFG-30L	8240123495	30	ISO 7-R 1 1/4"
280	TL3-BFG-30L	8240123495	30	ISO 7-R 1 1/4"
300	TL3-BFG-30L	8240123495	30	ISO 7-R 1 1/4"

Gama de sarcini termice ..... 20-300 kW  
 Intervalul de temperatura de intrare si iesire (partea calda) ..... 70°C-40°C  
 Intervalul de temperatura de intrare si iesire (partea rece) ..... 10°C-55°C

Cadere de presiune maxima ..... 30 kPa  
 Materialul placii ..... Alloy 316  
 Materialul garniturii de etansare .....NBRP

Sarcina termica (kW)	Model Alfa Laval	Numarul articolului	Numar de placi	Tipul de conexiuni
20	T2-BFG-10H	8240125732	10	ISO 7-R 3/4"
40	T2-BFG-15H	8240125735	15	ISO 7-R 3/4"
60	T2-BFG-20H	8240125739	20	ISO 7-R 3/4"
80	M3-FG-20M	8240121681	20	ISO 7-R 1 1/4"
100	M3-FG-20M	8240121681	20	ISO 7-R 1 1/4"
120	M3-FG-25M	8240121682	25	ISO 7-R 1 1/4"
140	M3-FG-25M	8240121682	25	ISO 7-R 1 1/4"
160	M3-FG-30H	8240121694	30	ISO 7-R 1 1/4"
180	M3-FG-35H	8240121695	35	ISO 7-R 1 1/4"
200	M3-FG-35H	8240121695	35	ISO 7-R 1 1/4"
220	TL3-BFG-30L	8240123495	30	ISO 7-R 1 1/4"
240	TL3-BFG-35L	8240123500	35	ISO 7-R 1 1/4"
260	TL3-BFG-40L	8240123504	40	ISO 7-R 1 1/4"
280	TL3-BFG-40L	8240123504	40	ISO 7-R 1 1/4"
300	TL3-BFG-70M	8240123427	70	ISO 7-R 1 1/4"

# Incalzirea apei de la robinet

Gama de sarcini termice ..... 20-300 kW  
 Intervalul de temperatura de intrare si iesire (partea calda) ..... 90°C-60°C  
 Intervalul de temperatura de intrare si iesire (partea rece) ..... 10°C-55°C

Cadere de presiune maxima ..... 30 kPa  
 Materialul placii ..... Alloy 316  
 Materialul garniturii de etansare .....NBRP

Sarcina termica (kW)	Model Alfa Laval	Numarul articolului	Numar de placi	Tipul de conexiuni
20	T2-BFG-10H	8240125732	10	ISO 7-R 3/4"
40	T2-BFG-10H	8240125732	10	ISO 7-R 3/4"
60	T2-BFG-10H	8240125732	10	ISO 7-R 3/4"
80	T2-BFG-15H	8240125735	15	ISO 7-R 3/4"
100	T2-BFG-20H	8240125739	20	ISO 7-R 3/4"
120	M3-FG-20M	8240121681	20	ISO 7-R 1 1/4"
140	M3-FG-20M	8240121681	20	ISO 7-R 1 1/4"
160	M3-FG-25M	8240121682	25	ISO 7-R 1 1/4"
180	M3-FG-25M	8240121682	25	ISO 7-R 1 1/4"
200	M3-FG-25M	8240121682	25	ISO 7-R 1 1/4"
220	TL3-BFG-30L	8240123495	30	ISO 7-R 1 1/4"
240	TL3-BFG-35L	8240123500	35	ISO 7-R 1 1/4"
260	TL3-BFG-40L	8240123504	40	ISO 7-R 1 1/4"
280	TL3-BFG-40L	8240123504	40	ISO 7-R 1 1/4"
300	TL3-BFG-70M	8240123427	70	ISO 7-R 1 1/4"